

## FIREMAN SABJ Boots



### Colors

Yellow



ATS sole  
(registered  
design)

Anti-  
perforation +  
Safety toe cap

Polymer toe cap\*

Composite anti-perforation  
mid-sole\*

Outside height (size 8): 370  
mm

Weight (size 8): 1900g / pair

Elastomer: fireproofed NBR /  
CR

(fireproofed  
nitrile/polychloroprene  
rubber)

### Reference: FIREMAN SABJ Boots (safety toe cap + anti-perforation mid-sole)

Excellent resistance to heat flow, heat contact, fire.

Excellent resistance to chemicals : fuels, oils, weak and diluted acids, solvents.

Excellent resistance to abrasion and cuts

Used with chemical protective suits (satisfy permeation tests according to EN 943-2).

### Comply with standards :

#### EN 15090 type 3 HI3

Boots for emergency situation and fire with toxic chemicals emission.

#### EN ISO 20345 S5 HRO SRC

- Heel shock absorption.
- Antistatic.
- Resistance to heat contact (HRO).

#### EN 13832-3 J P Q

- Boots highly resistant to chemicals :
- N-Heptane (J)
- Hydrogen peroxide (P)
- Isopropanol (Q)

#### EN 13287

- Sole slip resistance (SRC) :
- Steel floor.
- Ceramic floor.

Marine fire protection equipment certified by SEE-BG, notified body N°0736 .

\* Sizes 3 and 4.5 have steel toe cap and steel midsole.

### Sizes

|    |    |       |     |       |    |    |     |      |       |    |       |
|----|----|-------|-----|-------|----|----|-----|------|-------|----|-------|
| FR | 36 | 37/38 | 39  | 40/41 | 42 | 43 | 44  | 45   | 46/47 | 48 | 49/50 |
| UK | 3  | 4.5   | 5.5 | 7     | 8  | 9  | 9 ½ | 10 ½ | 11 ½  | 13 | 14    |

Please contact us for sizes 3 and 4.5 certificate.