Technische fiche / Fiche technique / Technical sheet



PRODUCT NUMBER: 1002884

Restraint Lanyard Polyamide Rope 12 mm - 2m + 2 karabiners

> Honeywell MILLER

Overview

Reference Number

1002884

Product Type

Fall Protection

Range

Restraint Lanyards

Brand

Miller by Honeywell

Brand formerly known as

MILLER

Industry

• Industry • Building and Construction

Product Use

A restraint lanyard is used to restrict the worker's movement to prevent him reaching a location where a fall hazard exists.

Features & Benefits

Feature

Lightweight, versatile restraint and fall arrest lanyards designed for maximum protection. Adapted rope for work requiring limited movement and where there is a sufficient potential fall distance. This 2-meter rope comes with a buckle and two karabiners.

Benefit

A restraint lanyard is used to restrict the worker's movement to prevent him reaching a location where a fall hazard exists.

Technical Description



Length

2m

Weight

0,360 kg

Breaking Strength

> 15 KN

Operating Temperature

-30°C to +50°C

Rope

Rope Raw Material

12mm Polyamide

Rope Breaking Strength

> 2500 daN

Rope Standard

EN 696

Connector

Connector Type

Туре

Connector Raw Material

Raw MaterialZinc-plated steel

Connector Opening

Opening17 mm

Connector Breaking Strength

Breaking Strength> 2500 daN

Connector Standard

StandardEN 362

Complementary Information

Connection lanyard: 3 strands twisted rope One screw karabiner and a loop Plastic thimble Protected splices

Certifications

≜ E.C. Declaration of Conformity

EC Category PPE

3

Quality Assurance

ISO 9001 / 2000

EC Certificate Number

0333 AFAQ/CTH

EC Attestation

EC Attestation

EC Attestation Number

0082/490/160/09/00/0291

Additional Information

User Manual

NT90004208 IND L

User Information Sheet

User manual

Packaging

EAN Code 7312559871257

© Honeywell International Inc.