Technische fiche / Fiche technique / Technical sheet



PRODUCT NUMBER: 1002907 ME52 - Shock-Absorbing Lanyard - 2m rope - 2xML00

> Honeywell <u>M</u>iller[®]

Overview

Reference Number 1002907

Product Type Fall Protection

Range Shock Absorbing Lanyards

Brand Miller by Honeywell

Industry

Industry
Building and Construction

Product Use

2m rope Shock-Absorbing Lanyard equipped with 2 screwgate karabiners

Features & Benefits

Feature

Made of a highly resistant and durable 23mm polyester webbing or 12mm Polyamid rope for increased durability. 2m rope shock absorbing lanyard equipped with 2 ML00 karabiners.

Benefit

Adapted to harsh work conditions and difficult work environments. The lanyards offer a better comfort in case of a fall. Small size tear off dissipating element, which reduces the weight and makes the lanyard easier to handle and carry. Come with a variety of attachments and designed to better meet fall protection needs.

Technical Description

Length

2m Weight

0.774 kg

Breaking Strength > 15 KN Operating Temperature -30°C to +50°C

Rope Raw Material 12mm Polyamide

Rope Breaking Strength

Safety Shop.be

Westkaai 7 - B2170 Merksem / Antwerpen Tel. 03 646 99 60 - Fax 03 646 00 25 info@safetyshop.be - www.safetyshop.be > 2940 daN

Rope Standard EN 696

Connector

Connector Type Typekarabiner

Connector Raw Material Raw Material Galvanised steel

Connector Opening Opening17mm

Connector Breaking Strength Breaking Strength> 2500 daN

Connector Standard StandardEN 362(04)

Energy Absorber

Energy Absorber Raw Material Polyamide 30mm

Energy Absorber Breaking Strength for linked element: > 3200 daN for unlinked element: > 1500 daN

Certifications

E.C. Declaration of Conformity

EC Category PPE

Quality Assurance ISO 9001 / 2000

EC Certificate Number 333

EC Attestation

EC Attestation Number 0082/042/160/03/99/0121 EXT N°01/03/99

Additional Information

User Manual NT90004208 IND L

User Information Sheet User manual

Packaging

EAN Code 7312559871363

© Honeywell International Inc.