# Technische fiche / Fiche technique / Technical sheet



# 2220Z1

VB3™

The VB3™ 2220Z1 LED light has dual super bright white LEDs that may never need replacing and provide over 30 hours of run time. The light is ATEX safe for use in hazardous Zone 1 (Category 2) locations. The VB3™ 2220Z1 LED is ideal for professionals who work in areas with high risk of explosion such as chemical, pharmaceutical, power, oil and gas, and fire



#### **DIMENSIONS**

Length

3.50" (8.9 cm)

#### **MATERIALS**

Body Clip Anti-static Impact Modified PC/PBT Anti-static Impact Modified PC/PBT

Contact Spring Retainer Stainless Steel

#### **COLOURS**

Black

High Visibility Yellow

#### LIGHT SPECS

Lamp Type

LED

#### **POWER**

**Battery Size** 

CR2032

**Battery Type** 

Lithium

**Battery Quantity** 

\_\_\_\_\_

**Batteries Included** 

yes

Volts

3.0v

#### WEIGHT

**Weight With Batteries** 

1.0 oz (28 gr)

Weight Without Batteries

0.9 oz (26 gr)

Packaged Weight

1.7 oz (48 gr)

#### **SWITCH**

**Switch Type** 

Head Flip to Activate



## **CERTIFICATIONS**

#### ATEX Zone 1

## OTHER

Minimum Pack6MilitaryyesPackage CodeC

FL1 STANDARD	HIGH
	9 LUMENS
$\Theta$	34h 0mins
	12m
	38cd
	IPX4

#### Peli

Document created on 01-18-21