

SICEN

Merapi



7850A2FEO



FLEXOTHANE[®]
ESSENTIAL

Parka d'hiver de pluie haute visibilité (RWS)

100% étanche / Protection contre le vent / Souple / Elastique / Très confortable / Léger /
Silencieux



Parka d'hiver de pluie haute visibilité (RWS)

Merapi - 7850A2FE0

Normes européennes:

- » EN ISO 20471 : 2013 / Class 3
 - » RWS 04/1995
 - » EN 471 - RWS - for fluor yellow : only striping
 - » EN 343 : 2003 + A1 : 2007 / Class 3-1
 - » CE
 - » EN ISO 13688 : 2013
- Doublure détachable:*
EN 14058 : 2004 / Class 1 x x x x

Extérieur:

- » Col droit
- » Capuche enroulée dans le col
- » Fermeture à glissière sous rabat à boutons-pression
- » 2 poches enfilées
- » Manches droites
- » Coutures soudées par haute fréquence
- » Longueur dorsale 85 cm (L)

Doublure détachable:

- » Polaire détachable
- » Coupe-vent en tricot en bas des manches
- » Ne peut pas être porté séparément
- » 1 poche intérieure

Tissu:

Flexothane® Essential: 100% tricot en polyester avec enduction PU; ± 170 g/m²

Tailles:

S - XXXL

Couleur:

- » FC1 Orange Fluo
- » FY1 Jaune Fluo

En combinaison avec:

6564 (p.126)

Conditionnement:

- » 5 pièces par boîte

Instructions de lavage et d'entretien:



SIOEN head office

Fabriekstraat 23
B-8850 Ardoonie
Belgium

T: +32 (51) 740 800

F: +32 (51) 740 962

www.sioen-ppc.com



Discover
our products

© 2016 SIOEN - Protection through Innovation, Flexothane®, Siopor® and the SIOEN logo are trademarks of the SIOEN Industries Group.

Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. The right is reserved to amend this information without prior notice.

All our technical files, style descriptions, presentations, designs and drawings, give the latest update of the standards and design or style features of each product. However, delivered products may comply with previous standards, design or style features. For that SIOEN disclaims any liability whatsoever. Contact our sales for full information if specific requirements are needed.